Technical data sheet
Revised: 2022-05-10

Floorcoat Natural Oil

Product Type: Drying oil.
Coverage: 5-10 m2/L.
Drying Time: Approx. 2 days, 20°C 55%RH.
Fully cured: See "Commissioning".
Cleaning: Mineral turpentine.
Storage: Above 5°C and up to 30°C. Not frost-resistant or suitable for direct sunlight.
Shelf Life: 12 months, unopened, frost-free, max 30°C.

The information in this document and all further references and recommendations that we provide regarding the use of our products are based on experience and standard conditions. Due to the many possible applications and processing conditions, this does not exempt the user from conducting their own tests or obtaining technical advice from the seller or manufacturer. No guarantee is given for the craftsmanship of work performed using our products, and documentation of this is the responsibility of the executing craftsman.

As experience shows that unwanted effects may occur with recoating, even when performed according to correct professional guidelines, the contractor is advised to consider these as necessary in relation to the customer.

Manufacturer recommendations and applicable standards must be followed. Our liability and responsibility comply with our general terms and conditions and are not extended by this information or our advice. Upon the release of new technical information, the validity of the previous version expires.

Application:
For indoor use, on all plank and parquet floors, where a golden appearance and enhanced wood structure are desired.

Instructions for Use:
The floor must be completely dry, sanded clean, and free of grease and dirt.Shake the container thoroughly before use.The oil is applied evenly in the wood grain direction on a small floor area at a time. Use a roller, sponge, or similar applicator. The oil should remain wet and glossy for approx. 15-30 minutes. If the oil dries out, apply more within this period.Excess oil is scraped off with a rubber scraper to the next section of the floor if applicable.Then, wipe the floor with cotton cloths or a polishing machine in the direction of the wood grain so that the floor appears uniform without excess oil.For highly absorbent wood types, a re-oiling is recommended after 24 hours.During the curing period, the floor should not be walked on or covered, and within the first 14 days after oiling, the floor must not be washed.Oil cloths must be burned after use to avoid spontaneous combustion.
AS WE CANNOT GUARANTEE THE RESULTS ON PREVIOUSLY LACQUERED FLOORS, A TEST APPLICATION AND INSPECTION MUST ALWAYS BE CARRIED OUT.

IMPORTANT: Read additional information in the product's technical data sheet.

Commissioning:
Careful use of the floor after 2 days. Heavier furniture and carpets should be placed after at least 7 days.

Cleaning and Maintenance:
Daily maintenance cleaning is simply vacuuming. When the floor is dirty, greasy, etc., it should be washed with a mild soap solution using a well-wrung cloth.For wear and tear, the floor should be washed with Floorcoat Floor Soap and re-oiled with the oil. Do not use brown soap, ammonia, or other strongly alkaline cleaning agents.