Technical Data Sheet

Floorcoat Natural and White Soap

Description:
Floorcoat Natural & White Soap is a highly effective cleaning and care product for untreated, lye-treated, and oil-treated wooden floors where a whitish or natural appearance is desired. The product contains resins and vegetable waxes that form a protective, dirt-repellent care film.

Product data:

- **Color:** Natural and White
- **Packaging:** 1L + 2.5L + 5L
- **Application:** Mop, floor applicator, or cloth
- **Consumption:** Depends on wood type, absorbency, and application method
- **Drying Time:** 20–30 min. per treatment (at 20 °C, 65% RH)
- **Storage:** Store frost-free in original, tightly closed packaging
- **Temperature:** +5 °C to max. +30 °C, avoid direct sunlight
- **Shelf Life:** 12 months unopened

Instructions for use:

The product can be used for post-treatment and ongoing maintenance of indoor wooden floors and wooden furniture.

<u>Initial treatment of newly sanded or untreated wooden floors or furniture</u>

1. Shake the container thoroughly before use.
2. Mix 1 part soap with 6 parts lukewarm water.
3. For best results, use 2 buckets: one for rinsing the mop or cloth and one for the clean soap mixture.
4. Apply the mixture in the direction of the wood grain using a mop, applicator, or well-wrung cloth.
5. Wash the floor 3–4 times, allowing 20–30 minutes of drying between each application.

6. When the floor is saturated and dry, it can be polished with a polishing machine fitted with a white pad to achieve a more durable and easy-to-clean surface.

Use: The floor can be taken into use once it is completely dry.

Ongoing cleaning and maintenance

- **Daily cleaning:** Vacuuming or cleaning with a mild soap solution 1:10
- **For stains or wear:** Clean with Wood Cleaner for deep cleaning of the floor. Finish with floor cleaning using a stronger soap solution, 1:6.
- **Periodic care:** Use 100–200 ml of soap dissolved in 5 liters of water to refresh and protect the floor.

Disclaimer:
The information in this document and all other references and recommendations that we provide in connection with advising on the use of our products are the result of experience and are based on standard conditions. Due to the many possible uses and processing conditions, we do not exempt the user from conducting their own tests or seeking technical advice from the seller or manufacturer. There is no guarantee of the craftsmanship of work with our products, and documentation of this is the responsibility of the executing craftsman. As undesired effects can occur with re-lacquering, despite the work being carried out according to correct craftsmanship regulations, it is recommended that the contractor, to the extent necessary, takes these into account towards the customer. Recommendations from the manufacturer and any current standards must be followed. Our liability and responsibility follow our general terms and conditions of business and are not extended by this information or our advice. When new technical information emerges, the old version becomes invalid.

Revised: 2025-09-04