Technical datasheet

FC Home Soap - Oiled Surfaces

Description:
FC Home Soap - Oiled Surfaces is used for cleaning surfaces treated with Floor Oil 2-Component. The soap is an effective floor cleaner that leaves a clean, matte surface.

The product does not leave greasy residue and is suitable for all types of mop systems. The soap is economical in use due to its high concentration.

Product Data:

- **Product Type:** Soap
- **Packaging:** 1 L + 2.5 L
- **Application:** Mop or floor cloth
- **Dosage:** Please refer to the instructions below
- **Drying Time:** 30–90 min. (at 20°C, 65% RH)
- **Storage:** Store frost-free in the original, tightly sealed container
- **Temperature:** +5°C to max. +30°C, avoid direct sunlight
- **Shelf Life:** 12 months unopened
- **Precautions for use:** Refer to the product's safety data sheet (SDS)

Instructions for use:
The product is intended for the daily cleaning and maintenance of oiled wooden surfaces. FC Home Soap - Oiled Surfaces gently cleans the surface and helps preserve the natural appearance of the wood. The product is suitable for both regular maintenance and more intensive cleaning, depending on the dosage used.

1. Always vacuum the floor before cleaning to remove loose dirt and dust.
2. For regular cleaning, mix 25 ml of FC Home Soap - Oiled Surfaces with 10 litres of warm water.
3. For heavily soiled floors, mix 50 ml of FC Home Soap - Oiled Surfaces with 10 litres of warm water.

4. Apply the solution using a floor mop or floor cloth, following the direction of the wood grain or floorboards.
5. To ensure the best cleaning result, we recommend using two buckets – one containing the soap solution and one containing clean water for rinsing the mop.
6. Use as little water as possible when cleaning the floor, and leave the floor as dry as possible to avoid damage to joints, edges, and other moisture-sensitive areas.
7. Always use a well-wrung mop or cloth to avoid over-wetting the surface.

Keep out of reach of children.

Ready for Use:

Let the floor dry for at least 15 minutes. The floor can be used once the surface is completely dry.

IMPORTANT: Read further information in the product's technical data sheet.

Disclaimer:
The information in this document and all other references and recommendations provided in connection with the use of our products are based on experience and standard conditions.
Due to the many possible applications and processing conditions, we do not exempt the user from conducting their own tests or obtaining technical advice from the seller or manufacturer.

No guarantee is given for the craftsmanship involved when using our products – responsibility for proper application and documentation lies with the contractor performing the work. As unwanted effects may occur during recoating, even when carried out according to correct professional guidelines, we recommend that the contractor, where necessary, make the customer aware of such risks.

Manufacturer recommendations and any applicable standards must be followed.
Our liability and responsibility are governed by our general terms and conditions and are not extended by this information or our advice. When new technical information is released, the previous version becomes invalid.

Revised: 2026-05-21