Technical Datasheet

FC Home Exterior Cleaner

Description:
FC Home Exterior Cleaner is used for cleaning all types of weathered and contaminated exterior wood surfaces prior to a protective oil treatment.

Product data:

- **Product type:** Neutral cleaning agent.
- **Packaging:** 2.5 L
- **Coverage:** Approx. 20–40 m^2/L, depending on the level of soiling
- **Dilution:** 1:10 with water
- **Storage:** Store above 5°C and below 30°C. Protect from frost and direct sunlight.
- **Shelf Life:** 12 months unopened, stored frost-free and at a maximum of 30°C.
- **Safety:** Refer to the product Safety Data Sheet (SDS).

Instructions for Use:

Apply FC Home Exterior Cleaner, diluted 1:10 with water, to the wood surface using a pump sprayer or paint roller. It is recommended to leave the wetted surface for approximately 20 minutes.

The wood surface should then be thoroughly cleaned, either manually or mechanically, using a scrubbing brush or rotary scrubbing pad until a fresh and clean wood surface is achieved. Keep the surface moist with additional cleaning solution throughout the cleaning process.

After cleaning, rinse and scrub the surface thoroughly with plenty of water and a scrubbing brush.

Allow the surface to dry for 24 hours before treating it with FC Home Decking Oil in the desired colour.

Commissioning:

The surface should be treated with a protective finish before being put into service.

IMPORTANT: Please refer to the product's Technical Data Sheet for further information.

Disclaimer:
The information contained in this document, as well as all other references and recommendations provided in connection with the use of our products, is based on experience and standard conditions. Due to the many possible applications and processing conditions, users are not relieved of the responsibility to carry out their own tests or seek technical advice from the distributor or manufacturer.

No warranty is provided for workmanship carried out using our products, and documentation of such work remains the responsibility of the contractor. Undesirable effects may occur during recoating or retreatment, even when the work is performed according to proper trade practices. It is recommended that the contractor takes this into consideration and informs the customer where relevant.

The manufacturer's recommendations and any applicable standards must be followed. Our responsibility and obligations are governed by our general terms and conditions of sale and are not extended by this information or our advice. When new technical information becomes available, this version becomes obsolete.

Revideret: 2026-05-26