Technical datasheet

FC Home Maintenance Oil

Description:
FC Home Maintenance Oil is used as a post-treatment for refreshing and maintaining oiled wooden surfaces, including oiled wooden floors. It is recommended to use a clear or pigmented oil corresponding to the previously applied treatment.

Product data:

- **Product Type:** Drying oil.
- **Versions:** Clear and White
- **Coverage:** 50–75 m^2/L.
- **Drying Time:** Max. 12 hours, 20°C 55% RH.
- **Fully Cured:** See "Use".
- **Cleaning:** Mineral turpentine.
- **Storage:** Above 5°C and maximum 30°C. Protect from FROST and direct sunlight.
- **Shelf Life:** 9 months unopened, frost-free, max. 30°C.
- **Safety:** See the product Safety Data Sheet (SDS).

Instructions for Use:

Before treatment, ensure that the surface is clean, dry, and free from worn-through areas. Vacuum thoroughly before treating the floor. Apply the oil evenly and polish using a white polishing pad to achieve a uniform surface. Remove excess oil immediately. The oil should be applied at 20°C ± 5°C and 55% RH. Ensure good ventilation during drying to avoid drying issues. Do not cover the surface before the oil is completely dry. Oil-soaked cloths must be burned after use to avoid the risk of self-ignition.

AS WE CANNOT GUARANTEE AGAINST UNDESIRABLE CONDITIONS ON PREVIOUSLY OILED FLOORS, TEST APPLICATIONS AND INSPECTION MUST ALWAYS BE CARRIED OUT.

IMPORTANT: Read additional information in the product's technical datasheet.

Use:

Careful use of the floor after 1–2 days. Heavy furniture and rugs after a minimum of 2 days.

Cleaning and Maintenance:

After treatment, daily maintenance and cleaning consist only of vacuuming. When the floor becomes dirty, greasy, or similar, clean it using a mild soap solution and a firmly wrung cloth. Do not use soft soap, ammonia, or other strongly alkaline cleaning agents.

Disclaimer:
The information in this document, as well as all other references and recommendations provided in connection with advice regarding the use of our products, is based on experience and standard conditions. Due to the many possible applications and processing conditions, the user is not relieved of the responsibility to carry out their own tests or seek technical advice from the dealer or manufacturer.

No guarantee is given for the workmanship carried out using our products, and documentation of such workmanship is the responsibility of the performing contractor. Undesirable effects may occur during recoating, even if the work is carried out according to proper craftsmanship standards. It is recommended that the contractor takes this into consideration in relation to the customer where necessary.

The manufacturer's recommendations and any applicable standards must be followed. Our liability and obligations are governed by our general terms and conditions and are not extended by this information or our advice. When new technical information becomes available, previous versions become invalid.

Revised: 2026-05-21