FLOORCOAT

Technical datasheet

FC Home Oil Soap

Description:
FC Home Oil Soap is used for care, cleaning, and maintenance of oiled wooden surfaces. The oil soap adds extra oil to the wood, and it is therefore recommended to use either natural or white oil soap corresponding to the treated surface. Always clean using a firmly wrung cloth.

Product data:

- **Product Type:** Oil soap.
- **Packaging:** 1 L + 2.5 L
- **Mixing Ratio:** 1 part product to 20 parts water
- **Coverage:** Approx. 200 m^2/L, depending on the dilution ratio
- **Storage:** Store above 5°C and below 30°C. Protect from frost and direct sunlight.
- **Shelf Life:** 12 months unopened, stored frost-free and at a maximum of 30°C.
- **Safety:** See the product Safety Data Sheet (SDS).

Instructions for Use:
Shake the container before use. Ensure that the surface is clean and free from dust. Mix 1 part oil soap with 20 parts lukewarm water. Clean the surface using a firmly wrung cloth following the direction of the wood grain. Allow the surface to dry for at least 2 hours. The floor may be used once the surface is completely dry.

The surface must not be exposed to water for prolonged periods. For larger areas, it is recommended to divide the room into smaller sections.

Oiled surfaces should be treated regularly with maintenance oil. It is recommended to use FC Home Maintenance Oil.

FLOORCOAT

Use:

Allow the surface to dry for at least 2 hours. The floor may be used once the surface is completely dry.

Disclaimer:

The information in this document and all other references and recommendations that we provide in connection with advising on the use of our products are based on experience and standard conditions. Due to the many possible applications and processing conditions, the user is not relieved of the responsibility to carry out their own tests or seek technical advice from the seller or manufacturer. No guarantee is given for the craftsmanship of work carried out using our products, and documentation of such work is the responsibility of the performing contractor. As undesirable effects may occur during recoating, even when the work is carried out according to proper craftsmanship standards, it is recommended that the contractor takes this into consideration towards the customer where necessary. Recommendations from the manufacturer and any current standards must be followed. Our liability and obligations follow our general terms and conditions and are not extended by this information or our advice. When new technical information becomes available, previous versions become invalid.

Revised: 2026-05-21