Technical Data Sheet

FC Home Soap – Lacquered Surfaces

Description:
FC Home Soap - Lacquered Surfaces is an effective cleaner for lacquered wooden floors, LVT, cork, vinyl, and laminate floors as well as tiles. The product is suitable for use with all common mopping systems.

Product data:

- **Color:** Clear/pink
- **Packaging:** 1L + 2.5L
- **Application:** Mop or floor cloth
- **Dosage:** See instructions below
- **Drying Time:** 30–90 min. (at 20 °C, 65% RH)
- **Storage:** Store frost-free, in original, tightly closed packaging
- **Temperature:** +5 °C to max. +30 °C, avoid direct sunlight
- **Shelf Life:** 12 months unopened
- **Safety:** See the product Safety Data Sheet (SDS).

Instructions for use:

The product can be used for daily cleaning and maintenance of lacquered and other non-absorbent surfaces such as LVT, vinyl, and laminate. It is suitable for use in private homes, institutions, and commercial environments where an easy-to-clean and uniform surface is desired. FC Home Soap - Lacquered Surfaces is ideal for both regular maintenance and deeper cleaning, depending on dosage.

1. Always start by vacuuming the floor to remove loose dirt and dust.
2. For regular cleaning, mix 25 ml of FC Home Soap - Lacquered Surfaces in 10 liters of warm water.
3. For heavily soiled floors, mix 50 ml of FC Home Soap - Lacquered Surfaces in 10 liters of warm water.
4. Apply the solution with a floor mop or cloth along the length of the floorboards.
5. To ensure a clean washing result, it is recommended to use two buckets – one with the soap solution and one with clean water for rinsing the mop.
6. Wash the floor with as little water as possible and leave it as dry as possible to avoid damage to joints and edges.

Disclaimer:
The information in this document and all other references and recommendations that we provide in connection with advising on the use of our products are the result of experience and are based on standard conditions. Due to the many possible uses and processing conditions, we do not exempt the user from conducting their own tests or seeking technical advice from the seller or manufacturer. There is no guarantee of the craftsmanship of work with our products, and documentation of this is the responsibility of the executing craftsman. As undesired effects can occur with re-lacquering, despite the work being carried out according to correct craftsmanship regulations, it is recommended that the contractor, to the extent necessary, takes these into account towards the customer. Recommendations from the manufacturer and any current standards must be followed. Our liability and responsibility follow our general terms and conditions of business and are not extended by this information or our advice. When new technical information emerges, the old version becomes invalid.

Revised: 2026-05-20